OA9-2450/9207

COBHAM

Omni Antenna


The most important thing we build is trust

Designed for WLAN Applications Suitable for WIMAX/LTE Applications

High Gain


Rugged

Colour Options



Ø 50.10 [1.97]

MOUNTED VIA Ø57[2.24] SPIGOT



Elevation Pattern

ELECTRICAL	
Frequency	2.40 - 2.50 GHz
Gain	9 dBi Nom
Polarisation	Linear (Vertical)
Beamwidth	360° (Az) x 10° (El) Approx
Cross Polar	20 dB Typ
VSWR	1.5:1
Power Rating	25 W
Front to Back	N/A
Electrical Tilt	0°
MECHANICAL	
Standard Finish	Gloss White
Mass	1.5 Kg (0.05 oz)
Temperature	-40° to +60°C
Wind Loading	7.41 Kg (16.3 lbs) @ 100 mph
MOUNTING OPTIONS	
Kits Available	MK2/A
See separate data sheet	ts

SIDE VIEW N(F) CONNECTOR BASE VIEW Ø57[2.24]

908 [35.75]

50 [5.91]

GA: 9207

European Antennas Limited trading as Cobham Antenna Systems, Microwave Antennas European Antennas Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

The copyright of antenna designs and images is copyright protected and owned by European Antennas Limited. ©European Antennas Limited

Issued 240610

For further information please contact: Cobham Antenna Systems, Microwave Antennas Lambda House, Cheveley, Newmarket, Suffolk CB8 9RG, UK. Tel +44 (0)1638 732 177 Fax +44 (0) 1638 731999 Email newmarket.sales@cobham.com