SA17-60-3.5V/9301



Sector Antenna

The most important thing we build is trust


Designed for WiMAX/LTE Applications


Vertical Polarisation

Wide Band

High Gain

Adjustable Mounting Kit





	75 [2.80]	MOUNTED VIA 4 OFF M8 x 17 (0.67) STUDS
SIDE VIEW	200 [7.87] 50 [1.97] BASE VIEW	REAR VIEW N(F) CONNECTOR

ELECTRICAL	
Frequency	3.30 - 3.80 GHz
Gain	17.5 dBi Nom
Polarisation	Linear (Vertical)
Beamwidth	60° (Az) x 8° (El) Approx
Cross Polar	>24 dB Typ
VSWR	1.5:1 Max
Power Rating	50 W
Front to Back	>35 dB
Electrical Downtilt	1°
MECHANICAL	
Standard Finish	White LIV Stable Radome

Staridara i illisii	vvilite, o v Stable Radollie
Mass	3.5 Kg (7.7 lbs) Incl Packaging
Temperature	-40° to +60°C
Wind Loading	21.1 Kg (46.4 lbs) @ 100mph

MOUNTING OPTIONS

MODITING OF FIGHTS		
Kits Available	MK1/A	
See separate data sheets		

ADDITIONAL NOTES

European Antennas Limited trading as Cobham Antenna Systems, Microwave Antennas

European Antennas Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

Issued 200613

For further information please contact: Cobham Antenna Systems, Microwave Antennas Lambda House, Cheveley, Newmarket, Suffolk CB8 9RG, UK. Tel +44 (0)1638 732 177 Fax +44 (0) 1638 731999 Email newmarket.sales@cobham.com