DFPA-0.9L-1.9L/1823



Directional Antenna

The most important thing we build is trust


Designed for Security Applications


Dual Band


Left Hand Circular Polarised

Rugged

Compact







0.16

85.90 [3.38]



Frequency	824 - 960 MHz (0.9 Port)
	1.71 - 1.99 GHz (1.8 Port)
Gain	8.5 dBiC Typ. (Both Ports)
Polarisation	Left Hand Circular
Beamwidth	67° (Az) x 55° (El) (0.9 Port)
	60° (Az) x 43° (EI) (1.8 Port)
Axial Ratio	6 dB Typ
VSWR	2:1 Typ
Power Rating	25 W
Front to Back	>20 dB

MECHANICAL	
Standard Finish	White Radome
Mass	0.85 Kg (1.87 lbs)
Temperature	-20° to +50°C
Wind Loading	12.3 Kg (27.06 lbs) @ 100mph

MOUNTING OPTIONS Kits Available See separate data sheets

ADDITIONAL NOTES

ELECTRICAL

European Antennas Limited trading as Cobham Antenna Systems, Microwave Antennas

European Antennas Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

REAR

VIEW

GA: 1823

The copyright of antenna designs and images is copyright protected and owned by European Antennas Limited. ©European Antennas Limited

Issued 220311

For further information please contact: Cobham Antenna Systems, Microwave Antennas Lambda House, Cheveley, Newmarket, Suffolk CB8 9RG, UK. Tel +44 (0)1638 732 177 Fax +44 (0) 1638 731999 $Email\ antennasystems. ma@cobham.com$