FVD2-0.9V/1635



Flexible Omni Antenna


The most important thing we build is trust


Designed for IED Countermeasure Applications

Suitable for Manpack Applications

Suitable for Tactical Comms Applications

Ground Plane Independent





SIDE VIEW	200 [7.89] RIGID SECTION 462 [18.19] APPROX.	
BASE VIEW		
GA: 1635	N(M) CONNECTOR	/

FLECTRICAL	
Frequency	869- 960 MHz
Gain	0 dBi Nom
Polarisation	Linear (Vertical)
Beamwidth	360° (Az) x 80° (El) Approx
Cross Polar	15 - 20 dB Typ
VSWR	2:1
Power Rating	20 W
Front to Back	N/A
MECHANICAL	
Standard Finish	Matt Black
Mass	180 g (6.3 oz)
Temperature	-20° to +50°C
Wind Loading	N/A
MOUNTING OPTIONS	
Kits Available	N/A
See separate data sheet	:S

ADDITIONAL NOTES

European Antennas Limited trading as Cobham Antenna Systems, Microwave Antennas

European Antennas Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

The copyright of antenna designs and images is copyright protected and owned by European Antennas Limited. \bigcirc European Antennas Limited

Issued 120310

For further information please contact: Cobham Antenna Systems, Microwave Antennas Lambda House, Cheveley, Newmarket, Suffolk CB8 9RG, UK. Tel +44 (0)1638 732 177 Fax +44 (0) 1638 731999 Email newmarket.sales@cobham.com