OA2-0.15-0.60V/1664



Omni Antenna

The most important thing we build is trust


Designed for Electronic Warfare Applications


High Power

Wide Band

Low Azimuth Ripple

Rugged





Elevation Pattern

	806 [31.73]	
SIDE VIEW		
BASE VIEW	MOUNTED VIA 4 OFF M10 x 15 DEEP TAPPED HOLES, EQUI-SPACED ON 100 [3.94] PCD N(F) CONNECTOR	
GA: 1664	10 VI	

ELECTRICAL	
Frequency	150 - 600 MHz
Gain	2 dBi Nom
Polarisation	Linear (Vertical)
Beamwidth	360° (Az) x 80° (El) Approx
VSWR	2.5:1 Max 2:1 Typ
Power Rating	250 W
MECHANICAL	
Standard Finish	Olive Drab
Mass	4.2 Kg (9.24 lbs)

1112011111110112	
Standard Finish	Olive Drab
Mass	4.2 Kg (9.24 lbs)
Temperature	-20° to +50°C
Wind Loading	20.3 Kg (44.6 lbs) @ 100mph

MOUNTING OP	TIONS		
Kits Available	N/A		
See separate da	ta sheets		

Issued 180310

ADDITIONAL NOTES

European Antennas Limited trading as Cobham Antenna Systems, Microwave Antennas

European Antennas Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

The copyright of antenna designs and images is copyright protected and owned by European Antennas Limited. \bigcirc European Antennas Limited For further information please contact:
Cobham Antenna Systems, Microwave Antennas
Lambda House, Cheveley,
Newmarket, Suffolk CB8 9RG, UK.
Tel +44 (0) 1638 732 177
Fax +44 (0) 1638 731999
Email newmarket.sales@cobham.com