HDA-1.2V/1545

COBHAM

Blade Antenna

The most important thing we build is trust


Designed for Security Applications


Suitable for Man-Pack Applications

Pattern - Sectorial

High Gain

Lightweight





Elevation Pattern

ТОР	37.5 [1.48]		
VIEW	83]	SMA(M) CONNECTOR – ON 250mm OF RG316	
	46.5 [1.83		
	<u> </u>		
SIDE VIEW	-	81.5 [3.21]	END VIEW

ELECTRICAL	
Frequency	1.15 - 1.26 GHz
Gain	1.3 dBi Nom
Polarisation	Linear (Vertical)
Beamwidth	120° (Az) x 100° El) Approx
Cross Polar	12 dB Typ
VSWR	2.5:1 Max , 2:1 Typ
Power Rating	10 W
Front to Back	>10 dB
MECHANICAL	
Standard Finish	Grey ABS
Mass	30 g (1.06 oz)
Temperature	-20° to +50°C
Wind Loading	N/A
MOUNTING OPTIONS	
MOUNTING OPTIONS	

ADDITIONAL NOTES

European Antennas Limited trading as Cobham Antenna Systems, Microwave Antennas

European Antennas Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

GA: 1545

The copyright of antenna designs and images is copyright protected and owned by European Antennas Limited. \odot European Antennas Limited Issued 020910

For further information please contact:
Cobham Antenna Systems, Microwave Antennas
Lambda House, Cheveley,
Newmarket, Suffolk CB8 9RG, UK.
Tel +44 (0) 1638 732 177
Fax +44 (0) 1638 731999
Email newmarket.sales@cobham.com