
OA8-4.5H/1590


COBHAM

Omni Antenna

The most important thing we build is trust

Designed for WLan Applications Horizontal Polarisation Designed for Military Applications Suitable for Military Applications Rugged





SIDE VIEW	450 [17.72]		
BASE VIEW GA: 159	Ø 79 [3.11]	SMA(F) CONNECTOR MOUNTED VIA 4 OFF M6x10 TAPPED HOLES ON 63[2.48] PCD	

ELECTRICAL		
Frequency	4.40 - 4.60 GHz	
Gain	8 dBi Nom	
Polarisation	Linear (Hertical)	
Beamwidth	360° (Az) x 12° (El) Approx	
Cross Polar	30 dB Typ	
VSWR	2:1 Max	
Power Rating	20 W	
Front to Back	N/A	
MECHANICAL		
Standard Finish	Grey Radome	
Mass	450 g (1.0 lbs)	
Temperature	-40° to +60°C	
Wind Loading	5.7 Kg (12 lbs) @ 100mph	
MOUNTING OPTIONS		
Kits Available	N/A	

See separate data sheets

Issued 290610

ADDITIONAL NOTES

For further information please contact: Cobham Antenna Systems, Microwave Antennas Lambda House, Cheveley, Newmarket, Suffolk CB8 9RG, UK. Tel +44 (0)1638 732 177 Fax +44 (0) 1638 731999 $Email\ newmark et. sales @cobham.com$

European Antennas Limited trading as Cobham Antenna Systems, Microwave Antennas

European Antennas Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

The copyright of antenna designs and images is copyright protected and owned by European Antennas Limited.

©European Antennas Limited