## OMNI ANTENNA OA4-1.8V/1521



ELECTRICAL		SIDE		
FREQUENCY:	1.71 - 1.88 GHz	VIEW		
GAIN:	5 dBi Nom.			
POLARISATION:	Linear (Vertical)			
BEAMWIDTH:	360° (Az) x 44° (El) Approx.			
CROSS POLAR:	>25 dB			
VSWR:	2:1 Max. <1.5:1 Typ.			ISOMETRIC
POWER RATING:	50 W			VIEW
ELECTRICAL TILT:	10° Typ. Down		.41 S.1	
MECHANICAL			364 [14.34]	
STANDARD FINISH:	Gloss White			
MASS:	250g / 0.55 lbs			
TEMPERATURE:	-40° to +60°C			
WIND LOADING:	2.27 kg / 5.0 lbs @ 100 mph		2.64	
MOUNTING OF	TIONS			
KITS AVAILABLE:	MK7/A			
See Separate Data	Sheets			Ø 36 [1.42] SPIGOT
			Ø 36 [1.42]	
GA: 1521-2 DIMENSIONS: mm	lssued: <sup>#</sup> 280109 [inches] M	BASE VIEW		TOR

European Antennas Ltd. has a policy of continuous development and therefore stress that the data contained on this sheet should be used for guidance only.

European Antennas Ltd. is part of the Cobham Antennas Division





Certificate No 9268

European Antennas Ltd Lambda House, Cheveley Newmarket, Suffolk, CB8 9RG, UK Tel: +44 (0)1638 731888 sales@european-antennas.co.uk www.european-antennas.co.uk