
DLPA5-1945/1202




Directional Antenna

The most important thing we build is trust

Designed for Security Application Suitable for Multiple Applications Right Hand Circular Polarised Rugged





Elevation Pattern

160 [6.30] 20 120 [4.72]	MOUNTED VIA 4 OFF M5 THREADED INSERTS
7.3 [5.91]	0007
SIDE VIEW 60 02.85	2 OFF SMA(M) WITH INTEGRAL 5M RG58 CABLES
BASE VIEW GA: 1202	CABLES

ELECTRICAL		
Frequency	1.895 - 1.990 GHz	
Gain	4.8 dBiC Nom	
Polarisation	2x Right Hand Circular	
Beamwidth	62.5° (Az) x 53.3° (El) Approx	
Axial Ratio	3.1 dB Typ	
VSWR	2.0:1 Max	
Power Rating	20 W	
Front to Back	>30 dB	
MECHANICAL		
Standard Finish	Matt Black	

MECHANICAL	
Standard Finish	Matt Black
Mass	0.88 Kg (1.94 lbs)
Temperature	-20° to +50°C
Wind Loading	7.42 Kg (16.33 lbs) @ 100mph

MOUNTING OPTION	IS	
Kits Available	N/A	
See separate data sh		

Issued 151010

ADDITIONAL NOTES

European Antennas Limited trading as Cobham Antenna Systems, Microwave Antennas

European Antennas Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

The copyright of antenna designs and images is copyright protected and owned by European Antennas Limited. \bigcirc European Antennas Limited For further information please contact:
Cobham Antenna Systems, Microwave Antennas
Lambda House, Cheveley,
Newmarket, Suffolk CB8 9RG, UK.
Tel +44 (0) 1638 732 177
Fax +44 (0) 1638 731999
Email newmarket.sales@cobham.com