LPA7-455V/1206



Directional Antenna


The most important thing we build is trust


Designed for Commercial Applications

Suitable for DAS Applications


Low Profile

Rugged





Elevation Pattern



ELECTRICAL	
Frequency	440 - 470 MHz
Gain	8.4 dBi Nom
Polarisation	Linear (Vertical)
Beamwidth	73° (Az) x 65° (El) Approx
Cross Polar	19 dB Min
VSWR	1.5:1 Typ, 1.67:1 Worst Case
Power Rating	10 W
Front to Back	22 dB min
MECHANICAL	
Standard Finish	Alocrom 1200 and white radome
Mass	4.4 Kg (9.68 lbs)
Temperature	-20° to +50°C
Wind Loading	33 Kg (72 lbs) @ 100mph
MOUNTING OPTIONS	
Kits Available	N/A
See separate data sheet	ts

ADDITIONAL NOTES

Issued 221010

European Antennas Limited trading as Cobham Antenna Systems, Microwave Antennas

European Antennas Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

The copyright of antenna designs and images is copyright protected and owned by European Antennas Limited.

©European Antennas Limited

For further information please contact:
Cobham Antenna Systems, Microwave Antennas
Lambda House, Cheveley,
Newmarket, Suffolk CB8 9RG, UK.
Tel +44 (0) 1638 732 177
Fax +44 (0) 1638 731999
Email newmarket.sales@cobham.com