## FPA26-47V/1157



## **Directional Antenna**

## The most important thing we build is trust


Designed for Tactical Comms Applications


High Gain

C-Band Frequency

Vertical Polarisation

Rugged





Elevation Pattern

TOP 57 10 10 10 10 10 10 10 10 10 10 10 10 10	
75 [2.95]  OPTIONAL MK1 MOUNTS TO 2 - 4.5" PROVIDES 0 - 10°  4 OFF M8.0 STUDS  8 OFF M6.0 STUDS  N(F) CONNECTOR VIEW  82.20 [3.24]	POLE

ELECTRICAL	
Frequency	4.40 - 5.00 GHz
Gain	26.0 dBi Peak
Polarisation	Linear (Vertical)
Beamwidth	6° (Az) x 6° (El) Approx
Axial Ratio	>20 dB Typ
VSWR	2:1 Max, <1.5:1 Typ
Power Rating	10 W
Front to Back	>50 dB
MECHANICAL	
Constant Freed	01: 6

MECHANICAL		
Standard Finish	Olive Green	
Mass	4.1 Kg excl. Brackets	
Temperature	-40° to +60°C	
Wind Loading	58.4 Kg (128.5 lbs) @ 100mph	

## MOUNTING OPTIONS Kits Available MK1 See separate data sheets

ADDITIONAL NOTES

European Antennas Limited trading as Cobham Antenna Systems, Microwave Antennas

European Antennas Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

The copyright of antenna designs and images is copyright protected and owned by European Antennas Limited.  $\bigcirc$  European Antennas Limited Issued 021212

For further information please contact:
Cobham Antenna Systems, Microwave Antennas
Lambda House, Cheveley,
Newmarket, Suffolk CB8 9RG, UK.
Tel +44 (0)1638 732 177
Fax +44 (0) 1638 731999
Email newmarket.sales@cobham.com