FPA20-47R-TNC/1183



Directional Antenna

The most important thing we build is trust


Designed for Tactical Comms Applications


High Gain

C-Band Frequency

Right Hand Circular Polarised

Rugged





Elevation Pattern

TOP CONNECTOR VIEW
7651,40,43
8 OFF
M5 x 18 STUDS EQUI-SPACED ON 141.4 (5.57) PCD VIEW GA: 1183

ELECTRICAL	
Frequency	4.40 - 5.00 GHz
Gain	19.5 dBi Nom
Polarisation	Right Hand Circular
Beamwidth	14° (Az) x 14° (El) Approx
Axial Ratio	1.0 dB Typ
VSWR	>1.5:1
Power Rating	20 W
Front to Back	>50 dB
MECHANICAL	
Standard Finish	Matt Black
Mass	0.5 Kg (1.1 lbs)
Temperature	-40° to +60°C
Wind Loading	11.4 Kg (25.1 lbs) @ 100mph
MOUNTING OPTIONS	
	N/A

ADDITIONAL NOTES

Issued 021212

European Antennas Limited trading as Cobham Antenna Systems, Microwave Antennas

European Antennas Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

For further information please contact: Cobham Antenna Systems, Microwave Antennas Lambda House, Cheveley, Newmarket, Suffolk CB8 9RG, UK.

Tel +44 (0) 1638 732 177 Fax +44 (0) 1638 731999 Email newmarket.sales@cobham.com