VERTICALLY POLARISED OMNI ANTENNA VOA4-2150/1093



ELECTRICAL FREQUENCY: GAIN: POLARISATION: BEAMWIDTH: CROSS POLAR: VSWR: POWER RATING: FRONT TO BACK: MECHANICAL STANDARD FINISH:	2.0 - 2.25 GHz 4 dBi Min. Linear (Vertical) 360° (Az) x 40° (El) Approx. 20 dB Min. 2:1 Max. 50 W N/A Gloss White	SIDE VIEW		380 14.96	NOTE: THIS PRODUCT IS DC GROUNDED.
MASS:	185 g / 0.41 lbs				
TEMPERATURE:	–40° to +60°C			⊥	
WIND LOADING:	1.7 kg / 3.7 lbs @ 100 mph PTIONS			3.54	VIEW
KITS AVAILABLE:	N/A			06	
See Separate Data	Sheets			Y	\mathbf{O}
			36 1.42	Ť	MOUNTING VIA Ø 36 (1.42) SPIGOT
GA: 1093-3 DIMENSIONS: mm	lssued: " 091107 [inches]	END VIEW			-N(F) CONNECTOR 501093

European Antennas Ltd. has a policy of continuous development and therefore stress that the data contained on this sheet should be used for guidance only.

European Antennas Ltd. is part of the Cobham Antennas Division





Certificate No 9268

European Antennas Ltd Lambda House, Cheveley Newmarket, Suffolk, CB8 9RG, UK Tel: +44 (0)1638 731888 sales@european-antennas.co.uk www.european-antennas.co.uk