## SHROUDED HELIX ANTENNA AMHP14-2150R/453



ELECTRICAL		ТОР	1		
FREQUENCY:	2.0 - 2.3 GHz	VIEW			
GAIN:	14 dBiC				ISOMETRIC
POLARISATION:	Right Hand Circular	+			VIEW
BEAMWIDTH:	40° (Az) x 40° (El)				
AXIAL RATIO:	2.0 dB				
VSWR:	1.5:1	.5.			
POWER RATING:	20 W	Ø40[1.57	08		
FRONT TO BACK:	15 - 20 dB	D 4(			
			.50		
MECHANICAL		The second se	Ø 154.50 [6.08]		
STANDARD FINISH:	Matt Black		0.		
MASS:	1.0 kg / 2.2 lbs				
TEMPERATURE:	–20° to +50°C				
WIND LOADING:	3.9 kg / 8.7 lbs @ 100 mph				
<b>MOUNTING OF</b>	TIONS	[18.98]			AMPH14-21
KITS AVAILABLE:	MK3254				
See Separate Data	Sheets	482 [	1.7		Ť
		7	90 [ 3.54 ]		7
			<u> </u>		4
				N(F) CONNECTOR	2
					N N N N N N N N N N N N N N N N N N N
GA: 453-2	lssued: 290408	SIDE	¥		
DIMENSIONS: mm		VIEW	Φ37.50	[1 48]	50R/453

European Antennas Ltd. has a policy of continuous development and therefore stress that the data contained on this sheet should be used for guidance only.

European Antennas Ltd. is part of the Cobham Antennas Division





Certificate No 9268

European Antennas Ltd Lambda House, Cheveley Newmarket, Suffolk, CB8 9RG, UK Tel: +44 (0)1638 731888 sales@european-antennas.co.uk www.european-antennas.co.uk