FPA21-4.7VH/1998



Directional Antenna


The most important thing we build is trust

Designed for Security Application


Suitable for Tactical Comms Applications

Dual Lienar Polarisation

Rugged



Azimuth Pattern



Elevation Pattern

ELECTRICAL	
Frequency	4.40 - 5.00 GHz
Gain	22 dBi Typ
Polarisation	Dual Linear (Vert & Horiz)
Beamwidth	16° (Az) x 8° (El) Approx
Cross Polar	>30 dB
VSWR	2:1
Power Rating	25 W
Front to Back	>25dB
Electrical Tilt	0°
MECHANICAL	
Standard Finish	White
Mass	1.3 Kg (2.86 lbs)

ocarradra i inion	***************************************
Mass	1.3 Kg (2.86 lbs)
Temperature	-30° to +55°C
Wind Loading	20.4 Kg (44.9 lbs) @ 100mph
MOUNTING OPTIONS	<u> </u>

MOUNTING OPTIONS		
Kits Available	MK2/B	
See separate data sheets		

ADDITIONAL NOTES

SIDE 3.20 0.52 **VIEW** MOUNTED VIA 110 4.33 4 OFF M6 x 15 STUDS FOR MK2/B 5.91 11.10[0.44]2 OFF N(F) CONNECTORS **BASE VIEW** 105.80 100.50 262 10.31 **GA: 1998**

European Antennas Limited trading as Cobham Antenna Systems, Microwave Antennas

European Antennas Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

The copyright of antenna designs and images is copyright protected and owned by European Antennas Limited.

©European Antennas Limited

Issued 271113

For further information please contact:
Cobham Antenna Systems, Microwave Antennas
Lambda House, Cheveley,
Newmarket, Suffolk CB8 9RG, UK.
Tel +44 (0)1638 732 177
Fax +44 (0) 1638 731999
Email newmarket.sales@cobham.com