
OA2-2.5V-SM-FN/9613


Omni Spring Mount Antenna

Provisional Specification

The most important thing we build is trust







SIDE VIEW SPRING SECTION \$\times 20[0.8]\$ ENCAPSULATED N(M) CONNECTOR

ELECTRICAL

Frequency:	2.2 - 2.7 GHz
Gain:	4 dBiC Nom.
Polarisation:	Linear (Vertical)
Beamwidth:	360° (Az) x 70° (El) Approx.
Cross Polar:	>20 dB Typ.
VSWR:	2.5:1 Max 2:1 Typ.
Power Rating:	30 W
Front to Back:	N/A

MECHANICAL

Standard Finish:	Black
Mass:	300 g / 0.66 lbs Approx.
Temperature:	-40° to +60°C
Wind Loading:	N/A

MOUNTING OPTIONS

Kits Available: N/A
See Separate Data Sheets

DS: 9613-A Issued:
Dimensions: mm [inches]

021215

Chelton Limited trading as Cobham Antenna Systems, Microwave Antennas

Chelton Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this Data Sheet, no responsibility can be accepted for any errors or omissions.

The copyright of antenna designs and images is copyright protected and owned by Chelton Limited. ©Chelton Limited.

For further information please contact:

Cobham Antenna Systems, Microwave Antennas, Lambda House, Cheveley, Newmarket, Suffolk, CB8 9RG, UK

T: +44 (0) 1638 732177

E: newmarket.sales@cobham.com
W: www.cobham.com/antennasystems/

microwaveantennas