FPA25-103V/547

Directional Antenna




Key Features


X-Band

High Gain

Suitable for Outdoor Applications

Low Sidelobes





(similar product)

SMA(F) CONNECTOR **SIDE VIEW** HOLE PATTERN AS PER 12694-NNNN REV B0 **BASE VIEW BREATHER HOLE** WITH GORE-TEX VENT

ELECTRICAL

Frequency:	10.15 - 10.65 GHz
Gain:	25 dBiC Nom.
Polarisation:	Linear (Vertical)
Beamwidth:	7° (Az) x 7° (El)
Cross Polar:	30 dB Typ.
VSWR:	1.5:1 Max
Power Rating:	10 W
Front to Back:	35 dB

MECHANICAL

Standard Finish:	Grey RAL 9002 Semi Gloss
Mass:	1000 g / 2.2 lbs
Temperature:	−35° to + 75°C
Wind Loading:	10.14 Kg / 22.3 lbs @ 100 mph

MOUNTING OPTIONS

Kits Available: N/A See Separate Data Sheets

GA: 0547-1 **Issued:** 060111 Dimensions: mm [inches]

Chelton Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

contact: Chelton Limited, Lambda House, Cheveley, Newmarket, Suffolk CB8 9RG, UK. T: +44 (0)1638 732 177 E: newmarket.sales@chelton.com W: www.chelton.com/microwave

For further information please

The copyright of antenna designs and images is copyright protected and owned by Chelton Limited. ©Chelton Limited