

## OA7-2.0V/9009 Omni Antenna

## **Key Features:**

Designed for datalink applications

Vertical polarisation

**Rugged design** 

SIDE


VIEW


BASE VIEW

Ground plane independent

586.70[23.10]

Ø36[1.42]





## ELECTRICAL

Frequency:	1.920 to 2.175 GHz
Gain:	6.3 dBi Nom.
Polarisation:	Vertical
Beamwidth:	360° (Az) x 20° (El)
Cross Polar:	> 20 dB
VSWR:	2:1 Typ, 2.5:1 Max.
Power Rating:	50 W

## MECHANICAL

Standard Finish:	White
Mass:	321 g / 0.71 lbs
Temperature:	-40 to +60°C
Wind Loading:	30 N @ 100 mph

DC.	9009-3	Issued: 150223
Full r	radiation patterns	and CAD available on request

DS:	9009-3	Issu
Dim	ensions: mm [inches]	

Chelton Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this Datasheet, no responsibility can be accepted for <u>any errors or</u>

N(F) CONNECTOR

The copyright of antenna designs and images is copyright protected and owned by Chelton Limited. ©Chelton Limited.

0

Chelton Limited, Lambda House, Cheveley, Newmarket, Suffolk, CB8 9RG, UK T: +44 (0) 1638 732177 E: newmarket.sales@chelton.com W: www.chelton.com/microwave