

Cobham Antenna Systems

Microwave Antennas

COBHAM

Specialist Antenna Design and Manufacture
Antennas for RADAR

The most important thing we build is trust



Man Pack
Antennas



Antennas
for Light
Vehicles



Antennas
for
Armoured
Vehicles



Antennas
for Vehicles
on Patrol



Radar

FMCW, Pulse and Reflectometer



Radar for secure peacekeeping

Radar Antennas

There are a wide variety of radar systems operating across the RF spectrum and they all work on the principle of a high power pulse or CW transmitted RF signal being reflected from the 'target' and usually being received by the same (or nearby) antenna.

Cobham Antenna Systems, Microwave Antennas has developed antennas for radar in Stripline and Waveguide for CW Doppler, FMCW, fixed beam pulse, and reflectometer arrays.

The antenna characteristics are critical to the system performance in order to resolve the target image.

Sophisticated modelling techniques combined with 20 years of experience in the design of microwave antennas will provide customers with an efficient, reliable antenna that meets their exact requirements. The company's near-field spherical anechoic test chamber supplies accurate patterns and 3-D images to demonstrate compliance with customers' specifications.

Application: Single panel, 28dBi gain antenna used in the X-Band CW Doppler Radar System

BAE Systems commissioned Cobham Antenna Systems, Microwave Antennas to develop a series of high specification directional antennas as part of the receive and transmit antenna system for their CW Doppler Radar system.

The radar system architecture uses commercial components to provide improvements in operation, simplifying logistics support and minimizing life cycle costs. This system was provided to the UK Aberporth Test and Evaluation Range, operated by QinetiQ on behalf of the UK Ministry of Defence and has been supplied to other Test Ranges.

The equipment comprises high gain directional transmit and receive antennas, each of which is made up of 16 directional 28dBi gain panel (sub-array) antennas designed and manufactured by Cobham Antenna Systems.

By using an array of phase-matched antennas that are suitably spaced apart, and by controlling the power and phase to each antenna element, the final beam shape can be controlled by the operator to provide greatest system flexibility.



Panel antennas for CW Doppler Radar System, as front cover

Radar

FMCW, Pulse and Reflectometer

Small Aperture X-Band Radar

Cobham Antenna Systems has developed an all printed circuit (PCB), 30dBi gain X-band antenna.

The benefits of the use of PCBs are that the weight can be less than the traditional parabolic dish, and have a wider bandwidth than the equivalent waveguide-based structures.

A full corporate feed network allows control of phase and amplitude at each patch element to ensure that the -29dB sidelobes are maintained over the entire band.

The use of a multi-layer PCB allows the radiating elements to be separated from the feed


X-band panel antenna, 30dBi high gain, horizontal polarisation.



network, ensuring high level cross polar and sidelobe performance.

For higher gains and higher powers, Cobham Antenna Systems is designing hybrid waveguide-PCB flat panel antennas which

Flat panel antenna azimuth pattern shows 2.5° beamwidth and very low sidelobes




provide the benefits of PCB-based antennas, but without the associated inefficiencies.

High Speed Target Acquisition and Tracking System


MARK Resources based in Torrance, California used a set of directional antennas developed by Cobham Antenna Systems, Microwave Antennas in precise arrangement mounted on a specially designed frame to meet the requirements for their new C-band radar system.

The High-Speed Target Acquisition and Tracking System radar (the HSTAT system) was developed by MARK Resources under the SBIR program with the US Air Force. It is designed to image and track multiple clustered objects.


As part of the brief, Cobham Antenna Systems, designed the antennas and frame to guarantee isolation of at least 70dB between the transmit antenna and all five receive antennas, to ensure that the radar met its performance specification. The company's on-site anechoic test chamber, which is normally used for precision spherical antenna pattern measurements, was utilised to demonstrate compliance to the high levels of isolation.



Reflectometer array provided precision velocity measurement for munitions trials



The directional flat panel, high gain antenna with vertical polarisation, used in the reflectometer array



The company's on-site anechoic test chamber which is normally used for precision spherical antenna pattern measurements, was utilised to ensure compliance to the high levels of isolation required.

Spherical Near-Field Testing

The on-site spherical near-field test facility is an example of our commitment to enhancing development facilities and technical support service to customers.


This facility provides 3-D radiation pattern data to verify specifications and to ensure compliance with stringent radiation pattern envelopes where necessary. The far field radiation pattern of the antenna can be calculated in any direction, in any polarisation, circular or linear, at any angle.

Operating within 0.4GHz to 40GHz, it has full dynamic range performance down to 0.8GHz, and sufficient sensitivity to test antennas in the lower frequency range.

Testing times depend on antenna size in wavelengths and the number of measurement frequencies. Gain and directivity measurements can be provided as well as phase. This allows for phase and amplitude matching batches of antennas which is necessary for Spiral antennas used in Direction-Finding systems.

An additional benefit of the spherical near field test facility is the ability to perform back projections on to a given plane within the measurement sphere which helps identify potential material defects. It also helps in the design process to determine if there is

unwanted radiation off the feed circuit, which can be corrected at a very early stage, and the affects of coupling within a circuit that may otherwise cause amplitude or phase corruption within an array.



BROCHURES



2012 Catalogue



Total Capability




Antenna Testing



Ground Control



Electronic Warfare



Body Worn



Link 16



IED Countermeasures



WiMAX and LTE



Unmanned Systems



C-Band



Radar Systems

Cobham Antenna Systems

M: Cobham Antenna Systems, Lambda House
 Cheveley, Newmarket, Suffolk CB8 9RG, UK
 T: +44 (0)1638 732177
 F: +44 (0)1638 731999
 E: newmarket.sales@cobham.com



Chelton Limited trading as Cobham Antenna Systems
 Cobham Antenna Systems - Radar Issue 2, 2010-10
 ©Chelton Limited

Chelton Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof.
 Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.
 All photography is protected by copyright and is used with thanks to the respective owners.