## VOA6-4.7V/1489



## **Omni Antenna**

## The most important thing we build is trust


Designed for Air to Ground Telemetry Link


C-Band Frequency

Suitable for Ground Based Applications

Rugged

Ground Plane Independent





Elevation Pattern

SIDE VIEW	### ### ### ##########################	
BASE VIEW	MOUNTED VIA CONNECTOR	
GA: 1489	N(M) CONNECTOR	

ELECTRICAL	
Frequency	4.40 - 5.00 GHz
Gain	6 dBi Nom
Polarisation	Linear (Vertical)
Beamwidth	360° (Az) x 24° (El) Approx
Cross Polar	>25 dB Typ
VSWR	2:1 Max
Power Rating	50 W
Front to Back	N/A
MECHANICAL	
Standard Finish	Gloss White
Mass	140g (4.9 oz)
Temperature	-20° to +50°C
Wind Loading	1.14 Kg (2.5lbs) @ 100mph

N/A

## See separate data sheets ADDITIONAL NOTES

Kits Available

Issued 091210

European Antennas Limited trading as Cobham Antenna Systems, Microwave Antennas

European Antennas Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

The copyright of antenna designs and images is copyright protected and owned by European Antennas Limited.  $\odot$ European Antennas Limited For further information please contact:
Cobham Antenna Systems, Microwave Antennas
Lambda House, Cheveley,
Newmarket, Suffolk CB8 9RG, UK.
Tel +44 (0) 1638 732 177
Fax +44 (0) 1638 731999
Email newmarket.sales@cobham.com