## OA4-1.4V/1515



## **Omni Antenna**


## The most important thing we build is trust


Designed for Security Applications

Pattern - Directional

Low Azimuth Ripple

Suitable for Outdoor Applications





Elevation Pattern

	389.95 [15.35]
SIDE VIEW	
BASE VIEW	Ø25.20 [0.99]

N(M)
CONNECTOR

ELECTRICAL		
Frequency	1.35 - 1.45 GHz	
Gain	5.0 dBi Nom	
Polarisation	Linear (Vertical)	
Beamwidth	360° (Az) x 37° (El) Approx	
Cross Polar	22.7 dB Typ	
VSWR	2:1 Max,<1.5:1 Typ	
Power Rating	40W	
Front to Back	N/A	
MECHANICAL		
Standard Finish	Gloss White (RAL 9910)	
Mass	<260g (9.3 oz)	
Temperature	-40° to +60°C	

Temperature	-40° to +60°C	
Wind Loading	1.5 Kg(3.2 lbs @ 100mph	
MOUNTING OPTIONS		
Kits Available	N/A	
See separate data shee	ts	

## ADDITIONAL NOTES

European Antennas Limited trading as Cobham Antenna Systems, Microwave Antennas

European Antennas Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

**GA: 1515** 

The copyright of antenna designs and images is copyright protected and owned by European Antennas Limited.  $\bigcirc$  European Antennas Limited Issued 130510

For further information please contact:
Cobham Antenna Systems, Microwave Antennas
Lambda House, Cheveley,
Newmarket, Suffolk CB8 9RG, UK.
Tel +44 (0)1638 732 177
Fax +44 (0) 1638 731999
Email antennasystems.ma@cobham.com