## UWBA-15300/1221



## **Directional Antenna**

## The most important thing we build is trust

Designed for IED Countermeasure Applications


Ultra Wideband


Pattern - Directional

Right Hand Circular Polarised

Rugged

Low Profile





Elevation Patterr

704.98 [27.75]	OPTIONAL BROADBAND MATCHING UNIT BMU-25-500/1222
671 [26.42]	VSWR WITH BMU: <2.5:1, 150-500 MHz
TOP 671 [26.42] VIEW	
BASE VIEW N(F) CONNECTOR	45]
GA: 1221	MOUNTED VIA 8 OFF Ø 12 [0.47] HOLES.

ELECTRICAL	
Frequency	150 - 3000 MHz
Efficiency	2% @ 150 MHz, 55% @ 275 MHz
	60% @ 500 MHz, 80-90%
	above 1 GHz
Polarisation	Right Hand Circular
VSWR (Antenna only)	10:1 to 3.5:1, 150-275 MHz
	3.5:1 to 2:1, 275-500 MHz
	<2:1, 500-3000 MHz
Power Rating	100 W
MECHANICAL	
Standard Finish	Matt Black
Mass	5 Kg (11 lbs) Approx
Temperature	-40° to +60°C
MOUNTING OPTIONS	
Kits Available	N/A
	ts

## ADDITIONAL NOTES

Issued 041110

 $\hbox{European Antennas Limited trading as Cobham Antenna Systems, Microwave Antennas}$ 

European Antennas Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

For further information please contact: Cobham Antenna Systems, Microwave Antennas Lambda House, Cheveley, Newmarket, Suffolk CB8 9RG, UK. Tel +44 (0) 1638 732 177 Fax +44 (0) 1638 731999 Email newmarket.sales@cobham.com