
VOA4-2600/1140




Omni Antenna

The most important thing we build is trust

Designed for Broadcast Applicatioans Suitable for Multiple Applications Vertical Polarisation Suitable for Mobile Applications Mounting Options





	290 [11.42]
SIDE VIEW	90 [3.54]
N(F) CONNECTOR	
BASE VIEW	MOUNTED VIA ∅ 36 (1.42) SPIGOT ∅ 36 [1.42]

ELECTRICAL	
Frequency	2.50 - 2.70 GHz
Gain	4 dBi Nom
Polarisation	Linear (Vertical)
Beamwidth	360° (Az) x 43.5° (El) Approx
Cross Polar	>20 dB Typ
VSWR	1.5:1
Power Rating	50 W
Front to Back	N/A
MECHANICAL	
Standard Finish	Gloss White
Mass	175g (0.38 lbs)
Temperature	-40° to +60°C
Wind Loading	1.37 Kg(3.0 lbs) @ 100mph
MOUNTING OPTIONS	
Kits Available	MK4/A
See separate data sheet	S

European Antennas Limited trading as Cobham Antenna Systems, Microwave Antennas

European Antennas Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

GA: 1140

The copyright of antenna designs and images is copyright protected and owned by European Antennas Limited.

©European Antennas Limited

Issued 041110

For further information please contact: Cobham Antenna Systems, Microwave Antennas Lambda House, Cheveley, Newmarket, Suffolk CB8 9RG, UK. Tel +44 (0)1638 732 177 Fax +44 (0) 1638 731999 $Email\ newmark et. sales @cobham.com$