RC010-3450/487


COBHAM


Omni antenna

Rugged

The most important thing we build is trust

Designed for WiMax/LTE Applications
Suitable for Multiple Applications
Right Hand Circularly Polarised
High Gain





Elevation Pattern

| | 627 [24.69] | |
|--------------|--|-------|
| Side View | MOUNT VIA φ50 [1.97] SPIGOT |) ann |
| Base View | MOUNT VIA Ø 50 [1.97] SPIGOT N(F) CONNECTOR | |

| ELECTRICAL | |
|------------------|-----------------------------|
| Frequency | 3.35 - 3.35 GHz |
| Gain | 8 dBiC Min Nom |
| Polarisation | Right Hand Circular |
| Beamwidth | 360° (Az) x 12° (El) Approx |
| Axial Ratio | 3 dB Typ |
| VSWR | 1.5:1 |
| Power Rating | 10W |
| Front to Back | N/A |
| MECHANICAL | |
| Standard Finish | Gloss White |
| Mass | 1.1 Kg (2.4 lbs) |
| Temperature | -20° to +50°C |
| Wind Loading | 8.6 Kg (18.9lbs) @ 100mph |
| MOUNTING OPTIONS | |
| Kits Available | N/A |

ADDITIONAL NOTES

GA: 0487

European Antennas Limited trading as Cobham Antenna Systems, Microwave Antennas

European Antennas Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

Issued 280110

For further information please contact:
Cobham Antenna Systems, Microwave Antennas
Lambda House, Cheveley,
Newmarket, Suffolk CB8 9RG, UK.
Tel +44 (0)1638 732 177
Fax +44 (0) 1638 731999
Email newmarket.sales@cobham.com