VOA10-1900/232



Omni Antenna

The most important thing we build is trust


Pattern - Omni Directional


High Gain

Suitable for Security Applications

Suitable for Outdoor Applications

Rugged





SIDE VIEW N(F)— CONNECTOR	MOUNTED VIA	
	MOUNTED VIA	
BASE VIEW	φ57[2.24]	
GA: 0232	·	

ELECTRICAL	
Frequency	1.85 - 1.95 GHz
Gain	10 dBi Nom
Polarisation	Linear (Vertical)
Beamwidth	360° (Az) x 10° (El) Approx
Cross Polar	20 dB Typ
VSWR	1.5:1
Power Rating	25 W
Front to Back	N/A
MECHANICAL	
Standard Finish	Gloss White
Mass	1.5 Kg (0.68 lbs)
Temperature	-20° to +50°C
Wind Loading	11.6 Kg (25.4 lbs) @ 100 mph
MOUNTING OPTIONS	
Kits Available	MK4/C

ADDITIONAL NOTES

European Antennas Limited trading as Cobham Antenna Systems, Microwave Antennas

European Antennas Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

Issued 030910

For further information please contact: Cobham Antenna Systems, Microwave Antennas Lambda House, Cheveley, Newmarket, Suffolk CB8 9RG, UK. Tel +44 (0)1638 732 177 Fax +44 (0) 1638 731999 Email newmarket.sales@cobham.com