
RC05-2250/203


COBHAM

Omni Antenna

The most important thing we build is trust

Designed for Security Applications Suitable for Multiple Applications Right Hand Circular Polarised Suitable for Mobile Applications Compact





	\$\frac{242.50 \[\frac{9.67}{0.67} \]
SIDE VIEW	N(F) CONNECTOR
BASE VIEW GA: 0203	35 [1.38] 08 00 00 00

ELECTRICAL	
Frequency	2.20 - 2.30 GHz
Gain	5 dBiC Nom
Polarisation	Right Hand Circular
Beamwidth	360° (Az) x 40° (El) Approx
Axial Ratio	2 dB Typ
VSWR	1.5:1 Typ
Power Rating	10 W
Front to Back	N/A
MECHANICAL	
Standard Finish	Gloss White
Mass	1.2 Kg (2.6 lbs)
Temperature	-20° to +50°C
Wind Loading	4.7 Kg (10.3lbs) @ 100mph
MOUNTING OPTIONS	
Kits Available	N/A
See separate data sheet	:S

European Antennas Limited trading as Cobham Antenna Systems, Microwave Antennas

European Antennas Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

Issued 200410

For further information please contact: Cobham Antenna Systems, Microwave Antennas Lambda House, Cheveley, Newmarket, Suffolk CB8 9RG, UK. Tel +44 (0)1638 732 177 Fax +44 (0) 1638 731999 Email newmarket.sales@cobham.com