EVD2-3450/225



Rugged Omni Antenna

The most important thing we build is trust


Designed for Commercial Applications


Suitable for Multiple Applications

Suitable for Mobile Applications

Compact

Ground Plane Independent





Elevation Pattern

-	Ø14[0.55]		
	4		
	178 [7.01]		п
Side View	178		
	<u> </u>		
Base View		N(F) CONNECTOR	
GA: 02	25	Ø26[1.02]	

ELECTRICAL		
Frequency	3.40 - 3.60 GHz	
Gain	2 dBi Nom	
Polarisation	Linear (Vertical)	
Beamwidth	360° (Az) x 80° (El) Approx	
Cross Polar	15-20 dB Typ	
VSWR	2:1 max	
Power Rating	25 W	
Front to Back	N/A	
MECHANICAL		
Standard Finish	Matt Black	
Mass	120g (4.0 oz)	
Temperature	-20° to +50°C	
Wind Loading	0.5 Kg(1.0lbs) @ 100mph	
MOUNTING OPTIONS		
Kits Available	N/A	

See separate data sheets
ADDITIONAL NOTES

European Antennas Limited trading as Cobham Antenna Systems, Microwave Antennas

European Antennas Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

Issued 080711

For further information please contact:
Cobham Antenna Systems, Microwave Antennas
Lambda House, Cheveley,
Newmarket, Suffolk CB8 9RG, UK.
Tel +44 (0)1638 732 177
Fax +44 (0) 1638 731999
Email antennasystems.ma@cobham.com