OA2-4.8V/1840

Omni Antenna



The most important thing we build is trust

Key Features:

Designed for Security Application

Designed for Integrated Solutions


Suitable for Multiple Applications

 \emptyset 14[0.6]


SMA(M) CONNECTOR

Lightweight

Vertical Polarisation



Azimuth Polar Plot



Elevation Polar Plot

4 40 - 5 00 GHz

SIDE VIEW [6:5] £2





ELECTRICAL

Frequency:

rrequency.	1. 10 3.00 GHZ	
Gain:	2.4 dBi Nom.	
Polarisation:	Linear (Vertical)	
Beamwidth:	360° (Az) x 63° (El) Approx.	
Cross Polar:	>20 dB Typ.	
VSWR:	2:1	
Power Rating:	10 W	
Front to Back:	N/A	
Electrical Tilt:	0°	

MECHA NICA L

Standard Finish:	Matt Black
Mass:	16 g (0.56oz)
Temperature:	−20° to +50°C
Wind Loading:	N/A

MOUNTING OPTIONS

Kits	Available	: N/A	4
See	Separate	Data 9	Sheets

Chelton Limited trading as Cobham Antenna Systems, Microwave Antennas

Chelton Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this Data Sheet, no responsibility can be accepted for any errors or omissions.

The copyright of antenna designs and images is copyright protected and owned by Chelton Limited. ©Chelton Limited.

For further information please contact:

Cobham Antenna Systems, Microwave Antennas, Lambda House, Cheveley, Newmarket, Suffolk, CB8 9RG, UK

T: +44 (0) 1638 732177

E: newmarket.sales@cobham.com W: www.cobham.com/antennasystems/ microwaveantennas