SA16-60-2.2V/1939

Sector Antenna

COBHAM

The most important thing we build is trust

Key Features:


Designed for WLAN applications


Sectorial pattern

Vertical polarisation

High gain

Adjustable mounting kit available





(@2.2.0

75[3.0] MOUNTED VIA 4 OFF M8 x 17 **STUDS** 100 280 11.0 550 **SIDE** REAR **VIEW VIEW** 101[4.0] 200 [7.9] N(F) CONNECTOR 50[2.0] **BASE**

ELECTRICAL

Frequency:	2.0 to 2.4 GHz
Gain:	16 dBi Typ.
Polarisation:	Vertical
Beamwidth:	65° (Az) x 8.5° (El) Typ.
Cross Polar:	>20 dB Typ.
VSWR:	<1.5:1 Typ, 2:1 Max.
Power Rating:	50 W
Front to Back:	>20 dB Typ.
Electrical Tilt:	0°

MECHANICAL

Standard Finish:	White radome
Mass:	3.0 Kg / 6.6 lbs
Temperature:	-40 to +60°C
Wind Loading:	368 N @ 100 mph

MOUNTING OPTIONS

Kits Available: MK1/A (not included)
See Separate Data Sheets

DS: 1939-1 Issued: 270121 Dimensions: mm [inches]

Chelton Limited trading as Cobham Antenna Systems, Microwave Antennas

Chelton Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this Data Sheet, no responsibility can be accepted for any errors or omissions.

The copyright of antenna designs and images is copyright protected and owned by Chelton Limited. ©Chelton Limited.

For further information please contact:

Cobham Antenna Systems, Microwave Antennas, Lambda House, Cheveley, Newmarket, Suffolk, CB8 9RG, UK

T: +44 (0) 1638 732177

E: newmarket.sales@cobham.com W: www.cobham.com/antennasystems/ microwaveantennas