VOA10-2340/459


Omni antenna




Key Features

Designed for Commercial Applications
High Gain

Suitable for Ground Based Applications
Suitable for Outdoor Applications
Lightweight





Elevation Patter

	1008 [39.69]	150 [5.91]			
Side View	¥	4			
Base View	Ø5	57 [2.24]		─N(F) CON	NECTOR
GA: 0459			•		

ELECTRICAL			
Frequency	2.28 - 2.38 GHz		
Gain	10 dBi Nom		
Polarisation	Linear (Vertical)		
Beamwidth	360° (Az) x 10° (El) Approx		
Cross Polar	20 dB Typ		
VSWR	1.5:1 Typ		
Power Rating	25 W		
Front to Back	N/A		
MECHANICAL			
Standard Finish	White		
Mass	1.75 Kg (3.85 lbs)		
Temperature	-20° to +50°C		
Wind Loading	8.2 Kg(18lbs) @ 100mph		
MOUNTING OPTIONS			
Kits Available	N/A		
	S		

Issued 280110

Chelton Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

E: newmarket.sales@chelton.com W: www.chelton.com/microwave