LCO5-3450-H1/964




Omni Antenna




Designed for security applications

Left hand circular polarised

Rugged





SIDE VIEW SIDE VIEW VI3.5[0.53] VIEN VIEN

ELECTRICAL

Frequency:	3.35 to 3.55 GHz
Gain (Peak):	5 dBiC Typ.
Gain (Average):	4.5 dBiC Typ.
Polarisation:	Left hand circular
Beamwidth:	360° x 34° Typ.
Axial Ratio:	2 dB Typ.
VSWR:	<1.5:1 Typ, 2:1 Max
Power Rating:	10 W

MECHANICAL

Standard Finish:	White
Mass:	550 g / 1.21 lbs
Temperature:	–20 to +50°C
Wind Loading:	209 N @ 100 mph

Full radiation patterns and CAD available on request

DS: 0964-3 Issued: 190521 Dimensions: mm [inches]

Chelton Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this Datasheet, no responsibility can be accepted for any errors or omissions. The copyright of antenna designs and images is copyright protected and owned by Chelton Limited. Chelton Limited, Lambda House, Cheveley, Newmarket, Suffolk, CB8 9RG, UK T: +44 (0) 1638 732177 E: newmarket.sales@chelton.com W: https://chelton.com/microwave