
SA17-24V/556


Sector Antenna



Key Features

Designed for WLAN Applications Suitable for RFID Applications Low Profile Rugged





	TOP VIEW
13.60 [0.54]	149.80 [5.90]
	MOUNTED VIA 4 OFF M8x33 STUDS ON REAR
1140 [44.88]	N(F) -CONNECTOR 56 [2.20]
1140	601[23.66]
SIDE VIEW ,	REAR VIEW
GA: 0556	75[2.95]

ELECTRICAL	
Frequency	2.30 - 2.48 GHz
Gain	17 dBi Nom
Polarisation	Linear (Vertical)
Beamwidth	70° (Az) x 8° (El) Approx
Cross Polar	20 dB
VSWR	1.5:1 Typ, 2:1 Max
Power Rating	25 W
Front to Back	25 dB
Electrical Tilt	0°
MECHANICAL	
Standard Finish	White
Mass	2.4 Kg (5.28 lbs) (excl brackets)
Temperature	-20° to +50°C
Wind Loading	30 Kg (66 lbs) @ 100mph
MOUNTING OPTIONS	
Kits Available	MK1/B (included)

See separate data sheets ADDITIONAL NOTES

Issued 191110

Chelton Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

The copyright of antenna designs and images is copyright protected and owned by Chelton Limited. ©Chelton Limited

For further information please contact: Chelton Limited, Lambda House, Cheveley, Newmarket, Suffolk CB8 9RG, UK. T: +44 (0)1638 732 177 E: newmarket.sales@chelton.com W: www.chelton.com/microwave