DLPA4-915R-1800R/1215


Directional Antenna




Key Features

Colour Options

Designed for Security Applications
Suitable for Multiple Applications
Right Hand Circular Polarised
Rugged
Connector Options





160 [6.30] 120 [4.72] **MOUNTED VIA 4 OFF** M5 THREADED INSERTS 50 5.91 988 2.87 **SIDE** RED HEAT SHRINK **VIEW** 1800 MHz 23.70 [0.93] 60 2.36 **BLUE HEAT SHRINK** 915 MHz **BASE** 2 OFF SMA(M) WITH INTEGRAL 5.0m LMR240 ULTRAFLEX CABLES **VIEW GA: 1215**

ELECTRICAL	
Frequency	870- 960 MHz, 1.71-1.88 GHz
Gain	5.00 dBiC (GSM) 6.2 dBiC (DCS)
	Nom
Polarisation	2x Right Hand Circular
Beamwidth	80° x 60 (GSM),
	60° x 50° (DCS) Approx
Axial Ratio	2-5 dB
VSWR	2.0:1
Power Rating	20 W
Front to Back	>16 dB (GSM), >20 dB (DCS)
MECHANICAL	
Standard Finish	Matt Black
Mass	0.85 Kg (1.87 lbs)
Temperature	-20° to +50°C
Wind Loading	7.42 Kg (16.33 lbs) @ 100mph
MOUNTING OPTIONS	
Kits Available	N/A
See separate data sheet	CS .

Issued 201114

Chelton Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.