



Omni Antenna



Designed for Security Applications Pattern - Omni Directional Suitable for Mobile Applications Suitable for Integrated Solutions Rugged Design





CHELTON



FLECTRICAL

ELECTRICAL	
Frequency	2.28 - 2.70 GHz
Gain	4 dBi Nom
Polarisation	Linear (Vertical)
Beamwidth	360° (Az) x 40° (El) Approx
Cross Polar	>20 dB
VSWR	2:1 Max, 1.5:1 Typ
Power Rating	30W
Front to Back	N/A
MECHANICAL	
Standard Finish	Matt Black
Mass	140g/4.9ozs
Temperature	-30° to +70°C
Wind Loading	0.8kg/1.75lbs @ 100mph
MOUNTING OPTIONS	
Kits Available	N/A
See separate data sheets	

ADDITIONAL NOTES

Issued 050310

Chelton Limited has a policy of continuous development and stress that the information provided is a guide only and does not constitute an offer or contract or part thereof. Whilst every effort is made to ensure the accuracy of the information contained in this brochure, no responsibility can be accepted for any errors or omissions.

The copyright of antenna designs and images is copyright protected and owned by Chelton Limited. ©Chelton Limited

For further information please contact: Chelton Limited, Lambda House, Cheveley, Newmarket, Suffolk CB8 9RG, UK. T: +44 (0)1638 732 177 E: newmarket.sales@chelton.com W: www.chelton.com/microwave